




## Product Description

General	Adaflex 109 elastic is a 2-component, high solid polyurethane coating with max. 15% wt. of solvent.
Suitability	Anywhere an elastic, weather-resistant, waterproofing coating is required, e.g. as sealing of coatings in catching areas and transshipment points or the outside of tanks.
Advantages	Elastic, weather-resistant, non-yellowing, temporarily resistant to Euro and super unleaded gasoline.

## Specification

Mixing ratio	4: 1 by weight
Pot life	At 23 °C 1h (2h gel)
Curing	12 - 30°C, max. 90 % rel. Humidity. Rain water resistant after 3h at 23°C. Full mechanically and chemically resilient after 14 days
Consumption	200 g / m <sup>2</sup> at 100 µm, dry film thickness
Colour	Aluminium
Packaging	Units of 8 / 2 kg
Storage Life	12 months in originally sealed containers at ambient temperature
Art. No.	Comp. A W-D0081 Comp. B W-D0082

Application	
Subsurfaces	Adalastic 2000, old but well roughened alkyd resin coatings, steel, or galvanized surface with primer.
Processing	Without diluting agent. Large surfaces with roller. Minor surfaces with paint brush.
Mixing	Add the whole of the contents of the comp. B container into the comp. A container and mix both together well with a stirrer for 3 minutes.
Climatic conditions	12 - 30°C, max. 90% rel. humidity.

Safety Precautions	
Precautions to be observed	Safety measures should be taken in accordance with the material safety data sheet. Local legal, health and safety regulations apply.
Liability	The above information is based on numerous tests and many years of experience. Liability for the application of the described product cannot be accepted as the results largely depend on the proper treatment and application of the material.
Hazards information	<p>Comp. A</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">               Fire         </div> <div style="text-align: center;">               Exclamation Mark         </div> </div> <p>Comp. B</p> <div style="text-align: center;">               Exclamation Mark         </div>
Transport information	Comp. A UN 2735 Comp. B NO ADR