




Application	
Subsurfaces	Mineral base-surfaces shall be solid, clean and dry. Any cavities in the concrete should preferably be filled with Epoflex Klebmörtel. The residual humidity in the concrete should not exceed 4%.
Structures	As a primer/seal for mineral surfaces. consumption: 200-600 g/m ² . As a laminating resin with suitable grades of glass mats. consumption. 3 to 3.5 x weight of glass mats. As a mortar binding agent: 10% - 16% addition to the following exemplary: Sand mixture (or equivalent) 1/3 silica sand 0.1 - 0.3 mm 1/3 silica sand 0.5 - 0.75 mm 1/3 silica sand 0.8 - 1.2 mm
Mixing	Add the contents of the comp. B container completely to the comp. A container and mix the combination thoroughly for 3 min. with a stirrer.
Processing	Adaflex AB can be rolled, spread, cast, or laminated with standard tools.
Equipment needed	Hand-stirring machine or power-drill with stirrer, hot-air blower, possibly a de-humidifier.
Climatic conditions	Min. 10°C base-surface temperature; during application and hardening, the temperature shall never be less than 3 °C above the dew point!

Safety Precautions	
Precautions to be observed	Safety measures should be taken in accordance with the material safety data sheet. Local legal, health and safety regulations apply.
Liability	The above information is based on numerous tests and many years of experience. Liability for the application of the described product cannot be accepted as the results largely depend on the proper treatment and application of the material.
Hazards information	<p>Comp. A</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Health Hazard</p> </div> <div style="text-align: center;">  <p>Exclamation Mark</p> </div> <div style="text-align: center;">  <p>Environment</p> </div> </div>

	<p>Comp. B</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  Health Hazard </div> <div style="text-align: center;">  Exclamation Mark </div> <div style="text-align: center;">  Environment </div> <div style="text-align: center;">  Corrosion </div> </div>
<p>Transport information</p>	<p>Comp. A UN 3082 Comp. B UN 2735</p>