




Product Description

General	Two-component main coat based on polyurethane resin applied on steel, aluminum and galvanized metallic surfaces.
Suitability	Intermediate coating for the protection and refurbishment of storage tanks and chemical plants.
Advantages	Adapur WR Glimmer characteristics are high mechanical strength and chemical resistance and have an excellent weather resistance.

Specification

Mixing ratio	5: 1 by weight
Density of mixture	1.5 kg / dm ³
Pot life	Approx. 6 - 8 h at 20°C
Curing	Dust free 15 min Safe to touch after 3 h Painting dry after ca. 4 h
Consumption	130 g / m ² for 40 µm of dry film thickness
Packaging	Units of 20 / 4 kg
Storage life	24 months at 20°C in originally sealed containers
Art. No.	Comp. A W-D9264 Comp. B W-D9265 (rolling) Comp. B W-D9265-s (spraying)

Application	
Subsurfaces	The surfaces shall be free of impurities, corrosion products, moisture, oils greases etc.
Structures	Surface shall be primered before with Adacor Zink or Adacor Grund. As top layer shall be applied Adapur WR.
Processing	Shall be with pneumatic or airless spraying methods, or can be rolled or brushed. Immediately after finishing the paintwork shall be cleaned with thinner or cleaner
Mixing	Resin shall not be mixed with solvent.
Equipment cleaning	The equipment shall be cleaned immediately after the application.
Climatic conditions	The steel surface temperature must be at min. 10°C and at least 3°C above the dew point at any time during application and hardening! The temperature shall not be higher than 35°C.

Safety Precautions	
Precautions to be observed	Safety measures should be taken in accordance with the material safety data sheet. Local legal, health and safety regulations apply.
Liability	The above information is based on numerous tests and many years of experience. Liability for the application of the described product cannot be accepted as the results largely depend on the proper treatment and application of the material.
Hazards information	<p>Comp. A  Fire</p> <p>Comp. B  Fire  Exclamation Mark</p>
Transport information	Comp. A UN 1263 Comp. B UN 1263